

Air or Nitrogen Hurricane Product Range



Booster Model	Engine	Suction P (psi / bar)	Discharge P (psi / bar)	Capacity @ Suction P (cfm / m3/min)
B4 - 41 / 750**	JD 4045	350 / 24	750 / 52	1800 / 51
B4 - 41 / 900*	JD 4045	350 / 24	900 / 62	1400 / 40
B4 - 41 / 1000**	JD 4045	350 / 24	1000 / 69	1400 / 40
B7 - 41 / 1000	CAT C7	350 / 24	1000 / 69	2440 / 69
B7 - 42 / 2175	CAT C7	350 / 24	2175 / 150	1288 / 37
B7 - 43 / 3000	CAT C7	150 / 10.3	3000 / 207	500 / 14
B7 - 43 / 4000	CAT C7	320 / 22	4000 / 276	750 / 21
B7 - 44 / 5000	CAT C7	261 / 18	5000 / 345	530 / 15
B9 - 64 / 5000	CAT C9	174 / 12	5000 / 345	550 / 16
B13 - 62 / 2175	CAT C13	350 / 24	2175 / 150	1932 / 55 (2-stage) 2900 / 82 (1-stage)
B15 - 62 / 2175	CAT C15	350 / 24	2175 / 150	2576 / 73 (2-stage) 3392 / 96 (1-stage)
B15 - 63 / 3000	CAT C15	325 / 22.4	3000 / 207	1800 / 51
B15 - 63 / 4000	CAT C15	310 / 21.4	4000 / 276	1650 / 47
B18 - 62 / 2175	CAT C18	350 / 24	2175 / 150	2900 / 82 (2-stage) 3865 / 110 (1-stage)
B18 - 63 / 3000	CAT C18	325 / 22.4	3000 / 207	2000 / 57
B18 - 63 / 4000	CAT C18	325 / 22.4	4000 / 276	1900 / 54
B18TT - 63 / 5000	CAT C18 Twin Turbo	350 / 24	5000 / 345	2144 / 61
B18TT - 61 / 1000	CAT C18 Twin Turbo	350 / 24	1000 / 69	4500 / 128
Containerized Model	Engine	Suction P (psi / bar)	Discharge P (psi / bar)	Capacity @ Suction P (cfm / m3/min)
B15 - 62 / 2175 weatherproof	CAT C15	350 / 24	2175 / 150	2576 / 73
B18 - 62 / 2175 weatherproof	CAT C18	350 / 24	2175 / 150	2900 / 82
B18 - 62 / 2175 rig safe	CAT C18	350 / 24	2175 / 150	3865 / 109
B18 - 63 / 4000 rig safe	CAT C18	325 / 22.4	4000 / 276	1900 / 54
B18TT - 63 / 5000 rig safe	CAT C18 Twin Turbo	350 / 24	5000 / 345	2144 / 61
XAHS375 Zone2 (Tier1)	Iveco 7675si	Atmosphere	175 / 12	375 / 11
XATS1020 Zone2 (Tier1)	CAT C3406	Atmosphere	150 / 10.3	1020 / 29
XATS1020 Zone2 (Tier3)	CUM QSM11 ATEX	Atmosphere	150 / 10.3	1020 / 29
XRVO1550 Zone2 (Tier3)	CAT C32 ATEX	Atmosphere	365 / 25	1550 / 44
B9 - 64 / 5000 Zone2 (Tier3)	CAT C9 ATEX	320 / 22	5000 / 345	755 / 21
Compound Compressor Model	Engine	Screw Compressor (psi / bar)	Discharge P (psi / bar)	Capacity (cfm / m3/min)
SBM12 - 44 / 3000	CAT C12 marine	Atmosphere to 150 / 10	3000 / 207	500 / 14
SBM18 - 44 / 2700	CAT C18 marine	Atmosphere to 165 / 12	2700 / 186	800 / 23
SB7 - 44 / 2000	CAT C7	Atmosphere to 160 / 11	2000 / 138	320 / 9
SB13 - 44 / 2500	CAT C13	Atmosphere to 150 / 10	2500 / 172	600 / 17
SB15 - 44 / 1500	CAT C15	Atmosphere to 150 / 10	1500 / 104	800 / 23
SB18 - 44 / 2700	CAT C18	Atmosphere to 165 / 12	2700 / 186	800 / 23
903-85 / 2000	CUM V903	Atmosphere	2000 / 138	600 / 17

*For US, Canada, Europe and Japan

** For countries other than US, Canada, Europe and Japan

Atlas Copco

Sustainable Productivity



B4 - 41



B7-41



B7 - 42



B18 - 62



SB7 - 44



SBM18 - 44



B18 - 62 Rig Safe



B18 - 62 Weatherproof



XATS 1020 Zone2

Standard features:

- Automatic load/unload system
- Booster bypass manifold (single and 2-stage only)
- Engine speed adjustment
- Double acting concentric valves
- Watercooled booster block
- Precooler and suction scrubber tank
- Intercoolers and scrubber tanks (multi-stage models)
- Aftercooler
- Open skid with four point lifting*
- 24 volt DC starting and operating system
- Suction, interstage (multi-stage models) and discharge safety relief valves
- Full function instrument panel monitoring all pressures, temperatures and controls with full protection shutdown and fault indicators

Options:

- Automatic scrubber tank drain
- Cold weather kit (-20°F/-29°C)
- Manual louvers in front of coolers
- Low pressure switch at booster inlet
- Lights for night operation
- Weatherproof container
- ASME B31.3 welding standard
- Trailer
- Spark arrestor
- Overspeed shutdown
- Air starter
- Staging valves on 2-stage models
- Service packs
- Valve and piston kits

Other options, pressures, capacities: available on request

*B7-41 has single point lifting

Service You Can Rely On

Global Network – The Atlas Copco service organization is established in over 160 countries. Local customer centers and fully equipped mobile service vans are an integral part of the aftermarket network.

Advanced Technical Support – More than 1700 service technicians are continuously trained and updated on the latest product developments and servicing methods.

World Class Logistics – Genuine parts are delivered to your doorstep in record times, wherever you are.



Atlas Copco Hurricane LLC
Part of the Atlas Copco Group
Phone: +1 (317) 736-3800
www.atlascopco.com/hurricane